

PRODUCT DATA SHEET

T23 HD PRO-F SERIES

PREMIUM PERFORMANCE DIESEL ENGINE OIL

T23 HD PRO-F Series engine oil is an advance diesel engine oil formulated using premium high-quality base oils with advance engine oil additives providing excellent protection for high performance diesel engines.

T23 HD PRO-F Series engine oil exhibit superior control of carbon deposits, minimizing engine sludges formation and prevent corrosion to the internal engine parts.

APPLICATIONS

T23 HD PRO-F Series engine oil is recommended for naturally-aspirated or turbocharged diesel engines as well as off-highway equipment such as construction, mining and agriculture stationary engines. It is also suitable for gasoline engine where an API SG grade of oil is recommended.

BENEFITS

- Excellent anti-rust and anti-corrosion properties protects the engine against corrosion;
- Excellent detergency and dispersant properties resisting deposit and sludge formation;
- Superior wear and bearing corrosion control ensuring maximum protection to the engine.

Consult Owner Guide for specific application and suitability of the oil grade selected.

SPECIFICATIONS & STANDARDS

T23 HD PRO-F Series engine oil meets the performance standards of:

API CF-4/SG

TYPICAL PROPERTIES

PROPERTIES	TEST METHOD SAE J 300	TYPICAL RESULTS	
SAE Grade		15W40	20W50
Specific Gravity @ 15°C	ASTM D-4052	0.8699	0.8759
Flash Point, °C	ASTM D-92	220 (min)	220 (min)
Pour Point, °C	ASTM D-97	-24	-24
Kinematics Viscosity			
@ 40°C (cSt)	ASTM D-445	112.5	157.5
@ 100°C (cSt)	ASTM D-445	15.1	18.26
Viscosity Index	ASTM D-2270	140	129
TBN (mgKOH/g)	ASTM D-2896	10.45	10.14
Colour	ASTM D-1500	L1.5	1.5