



AW HYDRAULIC OIL SERIES

HIGH PERFORMANCE ANTI-WEAR HYDRAULIC OIL

T23 AW HYDRAULIC OIL series is a premium line of universal anti-wear hydraulic fluid blended using highly refined hydro-treated base stocks combine with high performance anti-wear additives, to ensure maximum protection to the hydraulic pumps in the hydraulic system.

T23 AW HYDRAULIC OIL series possesses excellent thermal and oxidation stability characteristic. It also exhibits excellent hydrolytic stability providing protection to hydraulic systems even in the presence of moisture.

T23 AW HYDRAULIC OIL series contain rust and corrosion inhibitors as well as anti-foaming agent providing complete protection to the hydraulic system. **T23 AW HYDRAULIC OIL series** offers a wide range of viscosity to suit all working requirements.

APPLICATIONS

T23 AW HYDRAULIC OIL series is recommended for use in hydraulic equipment including hydraulic presses, machines tools, agricultural and mining equipment and PTO system.

BENEFITS

- Good thermal stability and anti-oxidation characteristic;
- Outstanding hydrolytic stability ensuring longer fluid lifespan;
- Excellent protection against wear to the hydraulic pumps;
- Resist foaming.

Consult Owner Guide for specific application and suitability of the oil grade selected.

SPECIFICATIONS & STANDARDS

T23 AW HYDRAULIC OIL series meets the performance standards of:

- Denison HF-0, HF-1, HF-2
- DIN 51524 part II
- FZG A/8.3/90 load stage 10 Pass
- Cincinnati Machine P-68, P-69, P-70
- ISO 20763 (Conestoga) vane pump test

TYPICAL PROPERTIES

PROPERTIES	TEST METHOD	TYPICAL RESULTS				
ISO Viscosity Grade		32	46	68	100	
Specific Gravity @15°C	ASTM D-4052	0.8619	0.8669	0.8719	0.8902	
Flash Point, °C	ASTM D-92	220 (min)	220 (min)	220 (min)	220 (min)	
Pour Point, °C	ASTN D-97	-15	-15	-12	-12	
Kinematics Viscosity						
	@ 40°C (cSt)	ASTM D-445	32.98	45.76	66.95	100.00
	@ 100°C (cSt)	ASTM D-445	5.623	6.975	8.948	11.20
Viscosity Index	ASTM D-2270	109	109	108	100	
Colour	ASTM D-1500	L0.5	L0.5	L0.5	0.5	

T23 Lubricant is a registered trademark of T23 International Pte Ltd.

The information contained in this data sheet is believed to be accurate as of the date of print, however, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests conducted under normal laboratory conditions and is given as a guide only. It is the responsibility of the user to evaluate and use the products safely, to access suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheet are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility will be taken by T23 International Pte Ltd or its subsidiaries for any damage or injury resulting from abnormal use of the product, from failing to adhere to recommendations, or from hazards inherent in the nature of the product. All product and information supplied are provided under our standard conditions of sales and users are advised to ensure that they refer to the latest version of the data sheet. You should consult our local representative if you require any further information.